
Opis produktu

64753-24-500

Presence Detector flexTronics 12 m studio white
matt



Ogólne informacje

Typ produktu	64753-24-500
Kod zamówieniowy	2CKA006800A3027
Numer EAN	4011395293966
Opis katalogowy	Presence Detector flexTronics 12 m studio white matt
Opis	<p>Presence detector sensor with mixed light measurement. For switching lighting systems that depend on brightness and movement. Circular detection range (for installation height of 3 m): Seated persons up to Ø 10 m, walking persons up to Ø 12 m. Extension of the detection range by main unit/extension unit combination. On wall / on ceiling height: 35 mm For semiautomatic and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/duration-off function (8 hrs), IR service remote control necessary. With teach-in function of the brightness switching threshold, IR service remote control required.</p> <p>With brightness-independent test mode for evaluating the detection zone. With detection LED at test mode. Remote control possible via IR service remote control 6843. Adjustment elements accessible on the front side. Surveillance density: 72 sectors with 640 switching segments. Switch-off delay: approx. 1 min. - 30 min. or short-time pulse. Compatible with all ABB flexTronics inserts. For relay insert flex, 1gang, 64811 U-500. For series relay insert flex, 2gang, 64821 U-500. For e-contact insert flex, 1gang, 64814 U-500. For LED touch dimmer insert flex, 1gang, 64851 U-500. For extension insert flex, 64891 U-500.</p>

Installation

Instrukcje i podręczniki	2CKA000073B5245 2CKA000073B5246 2CKA000073B5247 2CKA000073B5248 2CKA000073B5249 2CKA000073B5250
Typ montażu	Flush Mounted Surface Mounted
Pozycja montażu	Ceiling

Dane techniczne

Arkusze danych, informacja techniczna	2CKA001673B9577
Karta danych, informacje techniczne (część 2)	2CKA000073B5216
Skala	12 m
Grupa produktowa	flexTronics
Minimalny czas przełączania	Switch-On 60 second [unit of time]
Typ czujnika	Passive infrared

Design

Materiał	Thermoplastic
----------	---------------

Kolor RAL	RAL 9016 - Traffic White
Kolor	studio white matt

Material Compliance

Dane RoHS	2CKA200000E7445
Status RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Deklaracja REACH	2CKA309999E9999
REACH Information	False - does not contains substances > 0.1 mass percentage
Szablon raportowania CMRT	9AKK108468A3363

Normy środowiskowe

Temperatura powietrza otoczenia	-5...45 °C
Stopień ochrony	IP20

Wymiary

Szerokość netto	94 mm
Wysokość netto	94 mm
Głębokość / długość netto	45.5 mm
Masa netto	85 g

Klasyfikacje

ETIM 9	EC000138 - Sensor element for movement sensor
eClass	V11.0 : 27144008
Kategoria WEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006800A3042	Relay insert 1 gang(s) 230 V	64811 U-500	1	sztuka
2CKA006800A3048	Standard Outputs 1 gang(s) 230 V	64814 U-500	1	sztuka
2CKA006800A3045	Relay insert 2 gang(s) 230 V	64821 U-500	1	sztuka
2CKA006500A0013	Dimmer insert Push button 1 gang(s) 230 V	64851 U-500	1	sztuka
2CKA006800A3051	Bus Coupling Units / Push Button Coupling Units 1 gang(s) 230 V	64891 U-500	1	sztuka
2CKA006899A2369	Presence Detector studio white matt	6883-24-500	1	sztuka

Kategorie

Produkty niskiego napięcia i systemy → Wiring Accessories - StandAlone Electronics → Presence Detector → Professional Series

