

Opis produktu

8161.2

Blind switch 230 V



Ogólne informacje

Typ produktu	8161.2
Kod zamówieniowy	2CLA816120A1001
Numer EAN	8427238016825
Opis katalogowy	Blind switch 230 V

Opis	Rated voltage: 230 V [~] , +10 % / -10 %
	Rated frequency: 50 Hz
	Suitable for blind, roller blind and awning drives with mechanical or electronic limit switch shut-off.
	With two 230 V multi-way input terminals (Up/Down) for group control.
	With operating mode switch for the following modes: normal, louvre, base station, position.
	Wind alarm, cleaning functions can be accommodated via extension input.
	For comfort timer control element 8565.31 or 8565.3
	Remote control also available with blind switches / push-buttons code 8144.X
	Running time: 3 min
	Outputs: 2 Normally open contact
	Rated current: 3 A, cos φ0.5
	Rated power: 690 VA
	Control/Signal outputs: 2,
	Temperature range (Device): 0 °C to 35 °C
	Included: fixing claws

Installation

Instrukcje i podręczniki	No document needed
Typ montażu	Flush Mounted

Rodzaj mocowania

Mounting with Claw
Mounting with Screw

Dane techniczne

Arkusz danych, informacja
techniczna

9AKK107046A0356

Liczba baterii

0

Electrical

Napięcie znamionowe (U_r)

230 V

Częstotliwość (f)

50...50 Hz

Maksymalna moc
przełączania

690 W

Design

Design Range

Platform 8100
Alba
Sky Niessen

Kolor

No color

Material Compliance

Szablon raportowania
CMRT

9AKK108468A3363

Normy środowiskowe

Temperatura powietrza
otoczeniaEksploatacja -5 ... +35 °C
Przechowywanie -5 ... +50 °C

Stopień ochrony

IP20

Wymiary

Szerokość netto

0.062 m

Wysokość netto

0.073 m

Głębokość / długość netto

0.073 m

Masa netto

0.16 kg

Charakterystyka zamówienia

ID produktu zastąpionego

2CL0816120

Certyfikaty i deklaracje (Numer dokumentu)

Deklaracja zgodności UE

No declaration needed

Klasyfikacje

ETIM 9	EC000615 - Venetian blind control unit
UNSPSC	39122200
Kategoria WEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Kategorie

Produkty niskiego napięcia i systemy → Wiring Accessories - Light Switch Ranges → Flush Mounted Inserts → Electronic Inserts

