

PRODUCT-DETAILS

JSD-HD4-320H26

JSD-HD4-320H26 Safety Control Devices



General Information

Extended Product Type	JSD-HD4-320H26
Product ID	2TLA920077R0000
EAN	4013614500701
Catalog Description	JSD-HD4-320H26 Safety Control Devices
Long Description	<p>The JSD-HD4-320H26 is a three-position enabling device with LEDs and two additional buttons, on top and front. The connection is realized via a spiral cable 2/10m with Cannon 12pol. male connector.</p> <p>Please be aware that the internal wiring isn't equivalent to the standard devices. To ensure the right function, please check the data sheet before ordering.</p> <p>Three-position enabling devices are used to allow limited movement of the machine when the operator is in the hazardous area, for example during commissioning, maintenance and <u>troubleshooting</u>.</p>

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Product Main Type	JSHD
Product Name	Safety Control Devices
Function	Three-position device used to allow a limited movement of the machine when the operator is in the dangerous area.
Sub-Function	1 front and 1 top auxiliary buttons
Status Indicator	Yes

Popular Downloads

CAD Dimensional Drawing	2CDC001079B0201
-------------------------	-----------------

Dimensions

Cable Length	2 m 10 m
Product Net Depth / Length	34 mm
Product Net Height	202 mm
Product Net Width	58 mm
Product Net Weight	1.1 kg

Safety Information

Performance Level (PL)	Up to e
B10d Value	Operations to Bottom Position 968 000 Operations to Middle Position 2 million

Technical

Communication Interface	Contacts
Connection Configuration	Spiral Cable Cannon Connector
Maximum Switching Current	Main Circuit 20 mA
Maximum Switching Voltage	Main Circuit 30 V
Number of Contacts NO	4
Rated Operational Current DC-12 (I_{θ})	(24 V) 0.02 A
Rated Operational Voltage	24 V DC

Environmental

Ambient Air Temperature	Operation -10 ... +50 °C
Degree of Protection	IP65
Material	Rubber: NBR Handle: Polyamid and Norv

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
RoHS Information	2CMT2022-006499
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Container Information

Package Level 1 Units	carton 1 piece
Package Level 1 Width	99 mm

Package Level 1 Depth / Length	255 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	1.3 kg
Package Level 1 EAN	4013614500701

Classifications

eClass	V11.0 : 27371238
ETIM 7	EC002571 - Agreement switch
ETIM 8	EC002571 - Agreement switch
ETIM 9	EC002571 - Agreement switch

Categories

Low Voltage Products and Systems → Control Products → Safety Products → Safety Control Devices → JSHD

