

PRODUCT-DETAILS

KSB-305R

KSB-305R Signal Beacon



General Information

| | |
|-----------------------|--|
| Extended Product Type | KSB-305R |
| Product ID | 1SFA616080R3051 |
| EAN | 7320500202821 |
| Catalog Description | KSB-305R Signal Beacon |
| Long Description | KSB-305R Light Element LED Red Permanent light |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85369001 |
| Product Main Type | KSB |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SFC151007C02_ |
| Instructions and Manuals | 1SFC151011M0201 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 0.075 m |
| Product Net Depth / Length | 0.097 m |
| Product Net Height | 0.075 m |
| Product Net Weight | 0.14 kg |

Technical

| | |
|--|---|
| Accessory Type | Signal towers and beacons |
| Color | Red |
| Enclosure Type NEMA | Type5 |
| Function | Permanent light |
| Lamp Type | LED |
| Rated Control Supply Voltage (U _s) | 24 V AC/DC |
| Rated Frequency (f) | 50 / 60 Hz |
| Rated Operational Voltage | 24 V AC/DC |
| Standards | CAN/CSA C22.2 No.14, IEC/EN 60947-1, IEC/EN 60947-5-1, UL 508 |

Environmental

| | |
|--|---|
| Ambient Air Temperature | Operation -20 ... +50 °C Storage -20 ... 50 °C |
| Degree of Protection | Front IP65 |
| Maximum Operating Altitude Permissible | Without Derating 2000 m |

Material Compliance

| | |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 2CMT2022-006479 |
| RoHS Information | 2CMT2022-006498 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA | 2CMT2023-006523 |
| WEEE B2C / B2B | Business To Business |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Certificates and Declarations

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMT2015-005456 |
|--------------------------------|-----------------|

Container Information

| | |
|--------------------------------|-------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 0.1 m |
| Package Level 1 Depth / Length | 0.08 m |

| | |
|------------------------------|---------------|
| Package Level 1 Height | 0.075 m |
| Package Level 1 Gross Weight | 0.14 kg |
| Package Level 1 EAN | 7320500202821 |

Classifications

| | |
|------------------------------------|----------------------------------|
| eClass | V11.0 : 27143210 |
| E-Number (Finland) | 2313599 |
| ETIM 6 | EC001042 - Signal tower complete |
| ETIM 7 | EC001334 - Continuous luminaire |
| ETIM 8 | EC001334 - Continuous luminaire |
| ETIM 9 | EC001334 - Continuous luminaire |
| IDEA Granular Category Code (IGCC) | 3937 >> Strobe or warning lights |
| Object Classification Code | P |
| UNSPSC | 39111706 |

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Signal Towers and Beacons

