



CE

Power **75 W**

Voltage **230 V**


Colour temperature **4000 K**

Light colour **Neutral white**


Beam angle **90 °**

Protection class **IP40**




 User manual



 Declaration of Conformity

Technical data:

| | |
|------------------------------|---|
| Product code | SLI047100NW_PW |
| Power | 75 W |
| Nominal current | 335 mA |
| Voltage | 230 V |
| Energy consumption | 75 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Power factor | 0.98 |
| Useful luminous flux* | 13500 lm (360°) |
| Luminous flux** | 12750 lm (360°) |
| Light efficiency | 180 lm/W |
| Colour temperature | 4000 K |
| Light colour | Neutral white |
| Beam angle | 90 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | DALI |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum/PC |
| Protection class | IP40 |
| Colour | White |
| Dimension (axbxc) | 1438x65x40 mm |
| For use | Inside |
| Assembly method | On the ceiling/Suspended |
| Application | INTERNAL |
| Made in | PRC |
| Other | Max ilość opraw na zabezpieczenie nadprądowe: , |



*Applies to the LED source used. **Luminaire luminous flux