

## O-range® one-gang box for thin boarding



### One-gang junction box for thin boardings

- for boarding that does not permit edge countersinking (e.g. metal-covered boarding)
- with thin holding ring

|  |                |
|--|----------------|
| <b>Order number:</b>   | <b>9068-76</b> |
| EAN:   | 4013456222564  |
| For panel thickness  | 0,2 - 40 mm    |
| Depth  | 61 mm          |
| Cut hole Ø   | 68 mm          |
| Device screws  | 2              |
| Conduit entries Ø 20 mm  | 4              |
| Cable entries 3 x 1.5 mm <sup>2</sup>                            | 4              |
| Cable entries 3 x 2.5 mm <sup>2</sup> or 5 x 1.5 mm <sup>2</sup> | 2              |
| Cable entries for low voltages                                   | 2              |
| Halogen-free   | Yes            |
| Packaging inner/dispatch   | 25/250         |

The low 35 mm installation depth makes the one-gang box ideal for installation in cavity walls with a small cavity. In addition, thanks to the zero tension technology, the one-gang box can be fitted securely in wall systems with thin boarding.

- With zero tension technology for thin boarding
- Low 35 mm installation depth
- Cable entries with integrated cable retention
- Device screws with flat countersunk head
- For cables up to Ø 11.5 mm

