

103
lm/W



Power	32 W	Voltage	230 V
Luminous flux*	3300 lm (120°)	Colour temperature	3000 K
Light colour	WW	Beam angle	120 °
IK	06	Protection class	IP20



 User manual





 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI035014WW
Power	32 W
Nominal current	154 mA
Voltage	230 V
Energy efficiency classe	E
Energy consumption	32 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.9
Useful luminous flux*	3300 lm (120°)
Luminous flux**	3200 lm (360°)
Light efficiency	103 lm/W
Colour temperature	3000 K
Light colour	WW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC
IK	06
Protection class	IP20
Colour	White
Dimension (axbxc)	295x1195x10 mm
Mounting hole	275x1175 mm
For use	Inside
Assembly method	podtynkowy, natynkowy, zwieszany
Application	INT
Made in	PRC



*Applies to the LED source used. **Luminaire luminous flux

Also available as SMART, DALI, DIM and version with CNBOP-PIB* certificate (valid only in Poland).