

# SILENA 2

WQJP09991

LED luminaire SILENA 2, with a power of 35 W, high light efficacy 110 lm/W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 50° gives directional light so that selected objects or surfaces can be better exposed. Designed for recessed mounting.



|                    |               |
|--------------------|---------------|
| Power              | <b>35 W</b>   |
| Colour temperature | <b>3000 K</b> |
| Beam angle         | <b>50 °</b>   |

|                           |              |
|---------------------------|--------------|
| Voltage                   | <b>230 V</b> |
| Colour of light           | <b>WW</b>    |
| Degree of protection (IP) | <b>IP20</b>  |

## Technical data

|                              |                  |
|------------------------------|------------------|
| Code                         | WQJP09991        |
| Power                        | 35 W             |
| Nominal current              | 167 mA           |
| Voltage                      | 230 V            |
| Energy consumption           | 35 kWh/1000h     |
| Frequency                    | 50HZ Hz          |
| Protection class             | II               |
| Power supply included        | +                |
| Manufacturer of power supply | TRIDNIC          |
| Power factor                 | 0.93             |
| Useful luminous flux*        | 3850 lm (360°)   |
| Luminous flux**              | 2800 lm (360°)   |
| Lamp efficacy                | 110 lm/W         |
| Colour temperature           | 3000 K           |
| Colour of light              | WW               |
| Beam angle                   | 50 °             |
| RA                           | 90               |
| Light source included        | +                |
| Producer of LED diodes       | CREE             |
| Uniformity of color SDCM max | 3                |
| Dimmable                     | OPC              |
| Working temperature range    | -20/+40 °        |
| Lifespan                     | 50000 h          |
| Housing material             | Aluminum         |
| Degree of protection (IP)    | IP20             |
| Colour                       | White            |
| Dimension (AxBxC)            | 187x150 mm       |
| Mounting hole                | Ø175 mm          |
| For use                      | Inside           |
| Assembly method              | Recessed         |
| Application                  | Inside           |
| Made in                      | PL               |
| Catalogue number             | SAL10PR03593050W |

## Related documents



 User manual



 Declaration of Conformity

