OVE Austrian Electrotechnical Association

Eschenbachgasse 9 | 1010 Wien | Austria

ZVR: 327279890 | www.ove.at

OVE Certification

Kahlenberger Str. 2A | 1190 Wien | Austria T +43 1 370 58 06 | certification@ove.at

Validity of ÖVE-Certificates can be checked at www.ove.at



Page 1 of 4

ÖVE-CERTIFICATE

including the entitlement to use the Austrian Safety Mark



Certificate No.: 43-227-04 Valid from: 2022 12 17

until: 2024 12 17

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

PC Electric Ges.m.b.H. Company:

Diesseits 145

4973 St. Martin im Innkreis

Austria

Product: Appliance inlets for industrial purposes

The products submitted by the applicant were type tested in accordance with the requirements of the technical standards and specifications listed in this certificate. OVE certifies the conformity of the listed products and those products manufactured strictly identical to the submitted ones (EN ISO/IEC 17067, Conformity Assessment Scheme Type 5).

The manufacturing process and the products are subject to ongoing surveillance based on harmonized European procedures. This certificate has been issued under the presumption and conditional on the fact that the applicant holds all necessary legal rights with regard to the product, presented for the testing and certification.

Results of testing are shown in file No(s).: TGM-VA EE 35800

Österreichischer Verband für Elektrotechnik

Head of OVE Certification


Digitally signed by T. Neumayer Digitally signed by I. Neumayer Email=t neumayer@ove.at

Dipl.-Ing. T. Neumayer



Wien, 2022 11 29









Certificate No.: 43-227-04

Date: 2022 11 29 Page 2 of 4

Manufacturer:

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

Factory location(s):

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

Tested and certified according to:

ÖVE/ÖNORM EN 60309-1:2013-03-01 ÖVE/ÖNORM EN 60309-2:2013-03-01

This certificate is the basis for the EU Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity of the certified product(s) with the listed standards as defined by the **EU Low-Voltage Directive 2014/35/EU**. For the presumption of conformity according to Art. 12 with the safety objectives according to Art. 3 of the Directive, transitional periods given in the Official Journal of the European Union have to be observed.

Product: Appliance inlets for industrial purposes

Type designation: Rating:	Trademark:		
572 Rated current: 32 A Insolation voltage: 50 V IP44 or IP44/IP54 Wall mounted appliance-inlet without minor keyway	PCE / ELCEE / METECEE		
592	PCE / ELCEE / METECEE		

Rated current: 32 A Insolation voltage: 50 V IP44 or IP44/IP54 Wall mounted appliance-inlet with minor keyway

OVE Certification





Certificate No.: 43-227-04

Date: 2022 11 29 Page 3 of 4

573 PCE / ELCEE / METECEE

Rated current: 32 A Insolation voltage: 50 V IP44 or IP44/IP54

Wall mounted appliance-inlet

without minor keyway

593 PCE / ELCEE / METECEE

Rated current: 32 A Insolation voltage: 50 V IP44 or IP44/IP54

Wall mounted appliance-inlet

with minor keyway

PCE / ELCEE / METECEE

Rated current: 32 A Insolation voltage: 50 V IP44 or IP44/IP54 Flanged appliance-inlet without minor keyway

692 PCE / ELCEE / METECEE

Rated current: 32 A Insolation voltage: 50 V IP44 or IP44/IP54 Flanged appliance-inlet with minor keyway

PCE / ELCEE / METECEE

Rated current: 32 A Insolation voltage: 50 V IP44 or IP44/IP54 Flanged appliance-inlet without minor keyway

693 PCE / ELCEE / METECEE

Rated current: 32 A Insolation voltage: 50 V IP44 or IP44/IP54 Flanged appliance-inlet with minor keyway









Certificate No.: 43-227-04

Date: 2022 11 29 Page 4 of 4

Typelist

Type	Poles	Position minor keyway [h]	Rated operating voltage V [V]	Frequency [Hz]	Minor keyway
572		-	20-25	50 und 60	without
592	Ī [12	40-50	50 und 60	with
		4		100-200	
	2	2	20-25 and 40-50	300	
		3		400	
		11		>400-500	
		10		DC	
573		-	20-25	50 und 60	without
		12	40-50	50 und 60	with
593		4	20-25 and 40-50	100-200	
	3	2		300	
		3		400	
		11		>400-500	
		10		DC	
672		-	20-25	50 und 60	without
	2	12	40-50	50 und 60	- with
692		4	20-25 and 40-50	100-200	
		2		300	
		3		400	
		11		>400-500	
		10		DC	
673		-	20-25	50 und 60	without
	3	12	40-50	50 und 60	with
693		4	20-25 and 40-50	100-200	
		2		300	
		3		400	
		11		>400-500	
		10		DC	

