


ALGINE BACKLIGHT

SLI035087NW_PW

LED panel ALGINE BACKLIGHT, with a power of 36 W, high light efficacy 119 lm/W. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	36 W	Voltage	230 V
Luminous flux*	4300 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	120 °
Degree of protection (IP)	IP20		

Technical data

Code	SLI035087NW_PW
Power	36 W
Nominal current	165 mA
Voltage	230 V
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4300 lm (360°)
Luminous flux**	3240 lm (360°)
Lamp efficacy	119 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Lifespan	26000 h
Housing material	STAL / Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x30 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Made in	PRC
Other	plastikowa ramka ,

Logistics data

Bulk packaging	10 pcs.
Quantity per pallet	100 pcs.

Related documents

 User manual Declaration of Conformity