

SLI035083CCT_PW_IP44

SLI035083CCT_PW_IP44

ALGINE PANEL BACKLIGHT 26W / 36W / 46W CCT 230V 90ST IP44 UGR19 300X1200X34MM BIAŁY 5 LAT GWARANCJI



Power	26 / 36 / 46 W	Voltage	230 V
Luminous flux*	6300 lm (360°)	Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT	Beam angle	90 °
UGR	19	Degree of protection (IP)	IP44

Technical data

Code	SLI035083CCT_PW_IP44
Power	26 / 36 / 46 W
Nominal current	200 mA
Voltage	230 V
Energy consumption	46 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.95
Useful luminous flux*	6300 lm (360°)
Luminous flux**	3120 / 4320 / 5520 lm (360°)
Lamp efficacy	137 lm/W
Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT
Beam angle	90 °
UGR	19
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Lifespan	50000 h
Housing material	Aluminum / Plastic
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	295x1195x34 mm
For use	Inside
Application	INT
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,