

NYMPHEA FLAT DUO CCT

SLI031046CCT_PW

Plafond NYMPHEA FLAT DUO CCT with the possibility of changing the light color (CCT), with a power of 24 W, high light efficacy 130 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 3000/4000/6000K, we can adjust the light color depending on our needs and preferences. It has a high IP54 rating, making it ideal for use in rooms with high humidity. Designed for surface mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

CCT**IP54**

Power	24 W	Voltage	230 V
Luminous flux*	3100 lm (360°)	Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT	Beam angle	120 °
Degree of protection (IP)	IP54		

Technical data

Code	SLI031046CCT_PW
Power	24 W
Nominal current	180 mA
Voltage	230 V
Energy consumption	24 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.55
Useful luminous flux*	3100 lm (360°)
Luminous flux**	2400 lm (360°)
Lamp efficacy	130 lm/W
Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT
Beam angle	120 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Lifespan	17000 h
Housing material	Plastic
Degree of protection (IP)	IP54
Colour	White
Dimension (AxBxC)	292x26 mm
For use	Inside
Assembly method	On the ceiling
Application	Inside
Made in	PRC
Other	Light color change function 3000K / 4000K / 6000K ,

Logistics data

Bulk packaging 20 pcs.



Related documents

 User manual Declaration of Conformity

