

## Radiation protection one-gang junction box for lead-lined radiation protection



STRAHLENSCHUTZ



## Radiation protection one-gang junction box

- One-gang junction box for lead-lined radiation protection walls in buildings
- Combination distance of 71 mm through single separation of the pre-embossed edge

|                                     |               |
|-------------------------------------|---------------|
| Order number:                       | 9074-03       |
| EAN:                                | 4013456543768 |
| For panel thickness                 | 7 - 40 mm     |
| Depth                               | 58,5 mm       |
| Cut hole Ø                          | 74 mm         |
| Fixing screw spacing                | 60 mm         |
| Cable entries of up to Ø 11.5 mm    | 2             |
| Support connectors for each package | 3             |
| Lead equivalent value [mm Pb]       | 2,5           |
| Halogen-free                        | Yes           |
| Packaging inner/dispatch            | 5/10          |

The KAISER radiation protection box for use in lead-lined walls protects against radiation used for medical purposes, e.g. in X-ray equipment. The radiation protection material with an integrated lead function component absorbs the dangerous X-ray radiation with a lead equivalent value of 2,5 mm Pb as effectively as 2,5 mm thick lead.

- Protection against X-rays
- For lead-lined radiation protection walls
- No health risks - no skin contact with lead function component
- Retrofitting is possible
- Fast installation without additional screening measures
- Maintains the wall's sound insulation protection

