

## Sound insulation electronics box



SCHALLSCHUTZ



### Sound insulation electronics box halogen-free

- Electronics box for sound insulation walls in buildings
- Also for use as a double box
- For equipment inserts and electronic components
- Can be combined with each other and also with a sound insulation one-gang junction box

|                                                   |                |
|---------------------------------------------------|----------------|
| <b>Order number:</b>                              | <b>9069-74</b> |
| EAN:                                              | 4013456537217  |
| For panel thickness                               | 7 - 40 mm      |
| Depth                                             | 70 mm          |
| Cut hole Ø                                        | 2 x 74 mm      |
| Centre distance                                   | 71 mm          |
| Conduit entries for DIN EN conduits up to Ø 25 mm | 4              |
| Cable entries of up to Ø 11.5 mm                  | 4              |
| for sound insulation walls up to                  | 78 dB          |
| Halogen-free                                      | Yes            |
| Packaging inner/dispatch                          | 5/50           |

Sound insulation electronics box for use in walls with increased demands on sound insulation. The sound insulation electronics box maintains the wall's sound insulation function and creates space for electronic switching devices, data boxes, cables and terminals. The electronics box makes possible population with cables and installation conduits up to M25.

- Maintains the wall's sound insulation protection
- Retrofitting is possible
- Also for use as a double box
- Extra-large terminal area for communications and network technology
- Additional space for electronic components (KNX actuators, relays, radio module, communications technology)

