


screw terminal block 1 level feed-through, 2.5 mm², blue

Series	CBD
Code	CBX12
Type	CBD.2 (Ex)i
HS code	85369010
Colour	blue
TECHNICAL FEATURES	
Function/Type	Feed-through
Rated cross-section	2.5 mm²
Connecting capacity	
Flexible wire	0.5-4 mm²
Rigid wire	0.5-4 mm²
Wire with ferrule - ferrule type	2.5 mm² – WP25/14
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	690 V
Maximum current (rated cross-section)	24 A
Caliber	A3
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	20 A / 25 A
Section (min-max)	20-12 (AWG)
Tightening torque value (UL)	0.6 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	400 / 630 V
Maximum current (rated cross-section)	24 A
Operating temperature Min/Max	-40 °C / +110 °C
Rated impulse withstand voltage / pollution degree	8 kV / 3
Insulation stripping length	13 mm
Tightening torque value (nom. / max.)	0.4 / 0.8 Nm
Width (pitch)	5.5 mm
Length	40.5 mm
Height mounted on TH35-7.5/TH35-15/G32	47 / 55 / 51 mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	–
Blue	CB2/PT (Ex)i (cod. CBX13)
Beige	CB2/PT (cod. CB111)
Thickness	1.5 mm
Cross-connection	
Model A)	PM/20/... (cod. PM2...)
Model B)	–
Rated current carrying capacity IEC/ATEX	24 A / 24 A
Switchable cross-connection	POS/11 (cod. POS11)
Multiple cross-connection bar	PMP/01/45 (cod. PMP01) 45 poles
Shunting screw and sleeve (Standard / Exe)	CPM/21 (cod. CPM21) – CPX/21 (cod. CPX21)
Protection cover	PRP/6 (cod. PRP06)
Coloured partition plate	DFU/1/R (cod. DU01R)
Cross-connection barrier	DFM/600 (cod. DF600)
Test plug socket	SDD/1 (cod. DD001) – PSD/D (cod. PD004)
Modular test plug	SDD/5 (cod. DD005)
End section for modular test plug	SD5/PT (cod. DD501)
Shielding bar	CBD/SH (cod. CB009) (1)
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) – CNU/10/61 (cod. NU1061S)
Single marking tag for pitch insertion	–
Warning plate	TQM/02 on 4 (cod. TQM02)
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	PR/DIN/...
APPROVALS AND MARKINGS	
   	



1 For more details on accessories, refer to the relevant chapters **2** (1) With the shield connection bar, for grounding, the insulation voltage is reduced to 200V

DESCRIZIONE DEL PRODOTTO

screw terminal block 1 level feed-through, 2.5 mm², blue