


screw terminal block 1 level feed-through, 10 mm², blue



Series	CBD
Code	CBX45
Type	CBD.10 (Ex)i
HS code	85369010
Colour	blue
TECHNICAL FEATURES	
Function/Type	Feed-through
Rated cross-section	10 mm ²
Connecting capacity	
Flexible wire	0.5-16 mm ²
Rigid wire	0.5-16 mm ²
Wire with ferrule - ferrule type	10 mm ² - WP100/21
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	1000 V
Maximum current (rated cross-section)	57 A
Caliber	B6
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	60 A
Section (min-max)	20-6 (AWG)
Tightening torque value (UL)	1.5 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	500 / 630 V
Maximum current (rated cross-section)	57 A
Operating temperature Min/Max	-40 °C / +110 °C
Rated impulse withstand voltage / pollution degree	12 kV / 3
Insulation stripping length	14 mm
Tightening torque value (nom. / max.)	1.2 / 1.9 Nm
Width (pitch)	10 mm
Length	44 mm
Height mounted on TH35-7.5/TH35-15/G32	55 / 63 / 59 mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	-
Blue	CB10/PT (Ex)i (cod. CBX44)
Beige	CB10/PT (cod. CB431)
Thickness	1.5 mm
Cross-connection	
Model A)	PM/10/... (cod. PM10...)
Model B)	-
Rated current carrying capacity IEC/ATEX	57 A / 57 A
Switchable cross-connection	POS/44 (cod. POS44)
Multiple cross-connection bar	PMP/04/25 (cod. PMP04) 25 poles
Shunting screw and sleeve (Standard / Exe)	CPM/03 (cod. CPM03) - CPX/03 (cod. CPX03)
Protection cover	PRP/7 (cod. PRP07)
Coloured partition plate	DFU/4/R (cod. DU04R)
Cross-connection barrier	DFM/700 (cod. DF700)
Test plug socket	SDD/2 (cod. DD002) - PSD/B (cod. PD002)
Modular test plug	-
End section for modular test plug	-
Shielding bar	CBD/SH (cod. CB009) (1)
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S)
Single marking tag for pitch insertion	-
Warning plate	TTM/04 on 3 (cod. TTM04) - TQM/04 on 4 (cod. TQM04)
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	PR/DIN/...
APPROVALS AND MARKINGS	



1 For more details on accessories, refer to the relevant chapters **2** (1) With the shield connection bar, for grounding, the insulation voltage is reduced to 200V

DESCRIZIONE DEL PRODOTTO

screw terminal block 1 level feed-through, 10 mm², blue