





Model	Material	Color	Width (mm)	Height (mm)	Length (mm)	Weight (g)
T0810	PA66	Yellow-green	70	15	15	1.5

screw terminal block 1 level earth connection, 70 mm²

Series	TEC
Code	T0810
Type	TEC.70/O
HS code	85369010
Colour	Yellow-green
TECHNICAL FEATURES	
Function/Type	Earth terminal blocks
Rated cross-section	70 mm ²
Connecting capacity	
Flexible wire	10-95 mm ²
Rigid wire	10-95 mm ²
Wire with ferrule - ferrule type	-
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Caliber	B11
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Section (min-max)	-
Tightening torque value (UL)	-
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Rated impulse withstand voltage / pollution degree	8 kV / 3
Insulation stripping length	25 mm
Tightening torque value (nom. / max.)	6 / 9 Nm
Width (pitch)	20.5 mm
Length	70 mm
Height mounted on TH35-7.5/TH35-15/G32	81.5 / 74 / - mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	-
Green	-
Thickness	-
Cross-connection	
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S)
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	-
APPROVALS AND MARKINGS	



* Same profile and dimensions of the corresponding terminals of the CBC and GPA series* No end plates required, already closed in yellow/green shells

DESCRIZIONE DEL PRODOTTO

screw terminal block 1 level earth connection, 70 mm²

Copyright © Cabur srl Sede legale Località isola Grande, 45 - 17041 Altare (SV) - Italia - Tel. 019-589991 - Fax 019-58999233 - E-mail: info@cabur.it

