

NEXT AVAILABILITY




GREY VERSION			EFS.2/GR Cat. No. EFS200GR		EFS.4/GR Cat. No. EFS400GR	
BLUEE VERSION			EFS.2/BL Cat. No. EFS200BL		EFS.4/BL Cat. No. EFS400BL	
TECHNICAL CHARACTERISTICS						
Function / type			"blade" switchable		"blade" switchable	
Rated cross-section			[mm²]	2,5	4	
Connecting capacity	Flexible	[mm²]	0,2 ÷ 4		0,2 ÷ 6	
	Rigid	[mm²]	0,2 ÷ 4		0,2 ÷ 6	
	Max. flexible with ferrule	[mm²]-ferrule type	2,5 - WP25/14		4 - WP40/16	
Maximum voltage AC/DC			[V]	630	630	
Electrical characteristics according to European standard IEC EN 60947-7-1			Maximum current (with cable from 2,5mm²)	[A]	-	-
Section			Caliber	A3	A4	
Electrical characteristics according to UL standard	Maximum voltage AC/DC	[V]	UL Pending		UL Pending	
	Maximum current (with cable from 2,5mm²)	[A]				
	Section Min-Max	[AWG]				
Rated impulse withstand voltage / pollution degree			8kV / 3		8kV / 3	
Insulation stripping length			[mm]	9	10	
Width			[mm]	5,2	6,2	
Length			[mm]	49,6	55,2	
Height mounted on TH35 / 15			[mm]	39,2	41,2	
Height mounted on TH35 / 7,5			[mm]	46,7	48,7	
Insulation material temperature index (EN 40216-1)			[°C]	130	130	
Plastic material			Polyamide UL94 V0		Polyamide UL94 V0	

APPROVALS

ACCESSORIES		TYPE	CAT. NO.	TYPE	CAT. NO.
End section	grey	EFC.2/PT/GR	EFC201GR	EFC.4/PT/GR	EFC401GR
	blue	EFC.2/PT/BL	EFC201BL	EFC.4/PT/BL	EFC401BL
	End section thickness [mm]	1,5		1,5	
"Easy Bridge" (PTC) cross connection	2 poles	EFB.2/2/R	EFB0202R	EFB.4/2/R	EFB0402R
	3 poles	EFB.2/3/R	EFB0203R	EFB.4/3/R	EFB0403R
	5 poles	EFB.2/5/R	EFB0205R	EFB.4/5/R	EFB0405R
	10 poles	EFB.2/10/R	EFB0210R	EFB.4/10/R	EFB0410R
	Rated current carrying capacity of jumper [A]				
Coloured partition red		DFE.1+1/R	DFE01	DFE.1+1/R	DFE01
Striscia di numerazione adesiva da 105mm		TAM10105AW	TAM10105AW	TAM10105AW	TAM10105AW
Single marking tag		CNU/10/51	NU1051S	CNU/10/51	NU1051S
Single marking tag for pitch insert		CNU/10/51	NU1051S	CNU/10/61	NU1061S
End bracket	Screw	BT/3	BT003	BT/3	BT003
	Snap-fit	BTO	BT007	BTO	BT007

NEXT AVAILABILITY



GREY VERSION		EFT.2/GR Cat. No. EFT200GR				EFT.2/S/GR Cat. No. EFT250GR	
BLUE VERSION		EFT.2/BL Cat. No. EFT200BL					
GREEN/YELLOW VERSION				EFTE.2 Cat. No. EFTE200			
TECHNICAL CHARACTERISTICS							
Function / type							
Rated cross-section		[mm²] 2,5		2,5		2,5	
Connecting capacity	Flexible	[mm²] 0,2 ÷ 4		0,2 ÷ 4		0,2 ÷ 4	
	Rigid	[mm²] 0,2 ÷ 4		0,2 ÷ 4		0,2 ÷ 4	
	Max. flexible with ferrule	[mm²]-ferrule type 2,5 - WP25/14		2,5 - WP25/14		2,5 - WP25/14	
Electrical characteristics according to European standard IEC EN 60947-7-1	Maximum voltage AC/DC	[V] 800		800		250	
	Maximum current (with cable from 2,5mm²)	[A] -		-		-	
	Section	Caliber A3		A3		A3	
Electrical characteristics according to UL standard	Maximum voltage AC/DC	[V] UL Pending		UL Pending		UL Pending	
	Maximum current (with cable from 2,5mm²)	[A]					
	Section Min-Max	[AWG]					
Electrical characteristics according to ATEX directive and IEC Ex standard	Maximum voltage AC/DC	[V] ATEX Pending		ATEX Pending		ATEX Pending	
	Maximum current (with cable from 2,5mm²)	[A]					
	Use temperatures MIN / MAX	[°C]					
Rated impulse withstand voltage / pollution degree		8kV / 3		8kV / 3		8kV / 3	
Insulation stripping length		[mm] 9		9		9	
Width		[mm] 5,2		5,2		5,2	
Length		[mm] 106,2		106,2		89	
Height mounted on TH35 / 15		[mm] 68,4		68,4		43,9	
Height mounted on TH35 / 7,5		[mm] 75,9		75,9		51,4	
Insulation material temperature index [EN 60216-1]		[°C] 130		130		130	
Plastic material		Polyamide UL94 V0		Polyamide UL94 V0		Polyamide UL94 V0	

APPROVALS

ACCESSORIES		TYPE	CAT. NO.	TYPE	CAT. NO.	TYPE	CAT. NO.
End section	grey	EFT.2/PT/GR	EFT201GR	EFT.2/PT/GR	EFT201GR	EFT.2/S/PT/GR	EFT251GR
	blue	EFT.2/PT/BL	EFT201BL	-	-	-	-
	End section thickness [mm]	1,5		1,5		1,5	
"Easy Bridge" (PTC) cross connection	2 poles	EFB.2/2/R	EFB0202R	EFB.2/2/R	EFB0202R	EFB.2/2/R	EFB0202R
	3 poles	EFB.2/3/R	EFB0203R	EFB.2/3/R	EFB0203R	EFB.2/3/R	EFB0203R
	5 poles	EFB.2/5/R	EFB0205R	EFB.2/5/R	EFB0205R	EFB.2/5/R	EFB0205R
	10 poles	EFB.2/10/R	EFB0210R	EFB.2/10/R	EFB0210R	EFB.2/10/R	EFB0210R
	Rated current carrying capacity of jumper [A]						
105mm adhesive numbering strip (20 terminal blocks)		TAM10105AW	TAM10105AW	TAM10105AW	TAM10105AW	TAM10105AW	TAM10105AW
Single marking tag		CNU/10/51	NU1051S	CNU/10/51	NU1051S	CNU/10/51	NU1051S
Single marking tag for pitch insert		CNU/10/51	NU1051S	CNU/10/51	NU1051S	CNU/10/51	NU1051S
End bracket	Screw	BT/3	BT003	BT/3	BT003	BT/3	BT003
	Snap-fit	BTO	BT007	BTO	BT007	BTO	BT007