




spring clamp terminal block for pluggable
connector, 2.5 mm², grey

Series	HVPC-CHP
Code	HVP910GR
Type	CHP.2D/GR
HS code	85366990, 85389099
Colour	grey
TECHNICAL FEATURES	
Function/Type	Female connector
Rated cross-section	2.5 mm ²
Connecting capacity	
Flexible wire	0.2-4 mm ²
Rigid wire	0.2-4 mm ²
Wire with ferrule - ferrule type	2.5 mm ² – WP25/14
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	500 V
Maximum current (rated cross-section)	24 A
Caliber	A3
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	–
Maximum current (rated cross-section)	–
Section (min-max)	–
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	–
Maximum current (rated cross-section)	–
Operating temperature Min/Max	–
Rated impulse withstand voltage / pollution degree	8 kV / 3
Insulation stripping length	10 mm
Width (pitch)	5.2 mm
Length	58 mm (1)
Height mounted on TH35-7.5/TH35-15/G32	67 / 75 / – mm (1)
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	CHP.2D/PT/GR (cod. HVP911GR)
Blue	–
Thickness	2.5 mm
Cross-connection	
Model A)	PTC/03/... (cod. PTC03...)
Model B)	PTP/03/... (cod. PTC03...)
Rated current carrying capacity IEC/ATEX	24 A
Cross-connection identification strip	PTC/SP (cod. PTC0990)
Coloured partition plate	DFH/1/R (cod. DH01R)
Cross-connection barrier	–
Test plug	SDD/1 (cod. DD001)
Modular test plug	SDH/5 (cod. DH005)
End section for modular test plug	SH5/PT (cod. DH501)
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) – CNU/10/51 (cod. NU1051S)
Single marking tag for pitch insertion	CNU/8/51 (cod. NU0851S)
End bracket	
TH35 screw type	–
TH35 snap-fit type	–
TH35 and G32 snap-fit type	–
DIN rail according to IEC 60715/TH35	–
APPROVALS AND MARKINGS	



* Suitable for pluggable CPH.2 pluggable connectors
1 For more details on accessories, refer to the relevant chapters2 (1) Dimensions with inserted connector

DESCRIZIONE DEL PRODOTTO

spring clamp terminal block 1 level feed-through, 1.5 mm², blue