

RECIP-SP1 per motori AC7500-1000-10000	RECIP-SP2 per motori AC7500-10000
RECIP-SP3 per motori AC7500-10000 con abbin. di avviamento	RECIP-SP4 per motori AC7500 con abbin. di avviamento




Protezione: i morsi dell'ACB possono essere protetti contro costati diretti e/o accidentali mediante apposite coperture **PR7** di diverse grandezze. Piccola, Media e Grandi in materiale trasparente ed autoadesivo. Tali coperture, della lunghezza fino a 300 mm, corrispondono all'ampiezza di quattro morsi allineati ed inseriti su supporti **SPS** anch'essi in materiale autoadesivo, che consentono la protezione di una delle due cerniere dei morsi. La protezione completa della morselliera si ottiene utilizzando due coperture, sovrapposti.

La **PREUS** è da usare quando i conduttori vengono dal retroquadro, oppure si vuole proteggere un punto di connessione non ancora allacciato.

high current terminal bolt connection, 70 mm², beige

Series	BCA
Code	BC100
Type	BCA.70/BB
HS code	85369010
Colour	Beige
TECHNICAL FEATURES	
Function/Type	Feed-through
Rated cross-section	70 mm²
Connecting capacity	
Flexible wire	10-120 mm²
Rigid wire	6-120 mm²
Wire with ferrule - ferrule type	25 mm – M6 (1)
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	800 V
Maximum current (rated cross-section)	192 A
Caliber	–
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	–
Maximum current (rated cross-section)	–
Operating temperature Min/Max	–
ensione impulsiva nom. / grado di inquinamento	3 kV / 3
Insulation stripping length	–
Tightening torque value (nom. / max.)	–
Widht (pitch)	38 mm
Length	90 mm
Height mounted on TH35-7.5/TH35-15/G32	– / – / 49 mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
Cross-connection	
Coloured partition plate	–
Connector protection cover	PRT/P (cod. PRT01) – PRT/G (cod. PRT03)
Cover support	SPS/1 (cod. SPS01)
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) – CNU/10/61 (cod. NU1061S)
End bracket	
TH35 screw type	–
TH35 snap-fit type	–
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	PR/DIN/...
APPROVALS AND MARKINGS	



* Bar to bar connection

1 For more details on accessories, refer to the relevant chapters

DESCRIZIONE DEL PRODOTTO

high current terminal bolt connection, 70 mm², beige