


Male / Female - Female Y connector

Code	IS41410N
Type	KX04MFFN
HS code	85366990
TECHNICAL FEATURES	
Application	Y type
Connector type	Male/ Female – Female
Max. applicable voltage	1500 Vdc
Max. applicable current	60 (M) / 30 (F1) + 30 (F2)
PIN diameter	4 (mm)
Pliers to use	
PIN material	Tinned Copper
Insulation material	PPE / PA
Contact resistance Rc	< 0.25 (mΩ)
Operating temperature range	-40...+85 (°C)
Protection degree	IP67
Flame class	UL94-V0
Packaging	30 (6 bag for every box, every single bag contains 5 Y connectors.)
ACCESSORIES	
Open-end spanner and unlocking tool	
cod. unlocking tool	IS4SBLOCKN
Quantity / Package	2 pieces
Caps	
Male	IS52400N
Female	IS51400N
Operating temperature range	-40...+85
Protection degree	IP67
Flame class	UL94-V0
Quantity / Package	50 pieces
SPARE COMPONENTS	
Plastic shell	
Metallic PIN wound on reel	
APPROVALS AND MARKINGS	



1 (1) IS41410N replace the code IS41410.2 (2) IS42420N replace the code IS42420.

DESCRIZIONE DEL PRODOTTO

Male / Female - Female Y connector