





Male Fly 10 mm² connector

Code	IS14242N
Type	KX04VM100N
HS code	85366990
TECHNICAL FEATURES	
Application	Cable type
Connector type	Male
Max. applicable voltage	1500 Vdc
Max. applicable current	60 (A)
Cable section	10 (mm²)
PIN diameter	4 (mm)
Pliers to use	
Fixed matrix	IS3110
PIN material	Tinned Copper
Insulation material	PPE / PA
Contact resistance Rc	< 0.25 (mΩ)
Nut Cap locking force	1.5 - 1.8 (Nm)
Operating temperature range	-40...+85 (°C)
Protection degree	IP67
Flame class	UL94-V0
Packaging	100 (10 bag for every box, every single bag contains 10 plastic shell and 10 metallic PIN.)
ACCESSORIES	
Open-end spanner and unlocking tool	
cod. unlocking tool	IS4SBLOCKN
Quantity / Package	2 pieces
Caps	
Male	IS52400N
Female	IS51400N
Operating temperature range	-40...+85
Protection degree	IP67
Flame class	UL94-V0
Quantity / Package	50 pieces
SPARE COMPONENTS	
Plastic shell	
Metallic PIN wound on reel	
APPROVALS AND MARKINGS	



1 (1) IS14242N replace the code IS14242.2 (2) IS24243N replace the code IS24243.

DESCRIZIONE DEL PRODOTTO

Male Fly 10 mm² connector