




- Suitable for diodes and resistors
- Small size



PRESENTATION PURPOSE ONLY



PRESENTATION PURPOSE ONLY



CODE	XCCM08SV		XCCM16SV		XCCM24SV	
TYPE	CCM08SV		CCM16SV		CCM24SV	
GENERAL TECHNICAL DATA						
Number of poles	8		16		24	
Version	single feed-through		single feed-through		single feed-through	
Input rated voltage	0...100 V ±10%		0...100 V ±10%		0...100 V ±10%	
Input rated current	4 A max. (on common)		4 A max. (on common)		4 A max. (on common)	
Operating temperature	-20...+60°C		-20...+60°C		-20...+60°C	
Standards approvals	—		—		—	
Overvoltage category /pollution degree	II / 2		II / 2		II / 2	
Protection degree	IP 00		IP 00		IP 00	
Connection terminal	2.5 mm² screw		2.5 mm² screw		2.5 mm² screw	
Status indication	—		—		—	
Dimensions	25x66x93 mm		47x66x93 mm		70x66x93 mm	
Approximate weight	—		—		—	
Housing material	UL94V-0 plastic material		UL94V-0 plastic material		UL94V-0 plastic material	
Mounting informations	vertical on rails, side by side		vertical on rails, side by side		vertical on rails, side by side	
APPROVALS	CE		CE		CE	
ACCESSORIES						
Mounting rail IEC60715 TH35 75	PR003, PR903, PR005, PR939		PR003, PR903, PR005, PR940		PR003, PR903, PR005, PR941	
Mounting rail IEC60715 TH35 15	PR007, PR907, PR006, PR940		PR007, PR907, PR006, PR941		PR007, PR907, PR006, PR942	
Marking tag	—		—		—	