

# LED GLS

WOJ+14716

LED source LED GLS 13 W with the possibility of changing the light color (CCT) with E-27 base and with the shape of a traditional light bulb. Thanks to the ability to change the color temperature (CCT) in the range 2700k / 3000k / 4000k / 5000k / 6500K, we can adjust the light color depending on our needs and preferences. It is characterised by a high light efficacy 115 lm/W. Wide beam angle 270° ensures even illumination of the room.

**CCT**

|                 |                       |                    |                                               |
|-----------------|-----------------------|--------------------|-----------------------------------------------|
| Power           | <b>13 W</b>           | Voltage            | <b>230 V</b>                                  |
| Luminous flux** | <b>1500 lm (360°)</b> | Colour temperature | <b>2700 / 3000 / 4000<br/>/ 5000 / 6500 K</b> |
| Colour of light | <b>CCT</b>            | Beam angle         | <b>270 °</b>                                  |
| Socket          | <b>E27</b>            |                    |                                               |

## Technical data

|                              |                                                         |
|------------------------------|---------------------------------------------------------|
| Code                         | WQJ+14716                                               |
| Power                        | 13 W                                                    |
| Nominal current              | 100 mA                                                  |
| Voltage                      | 230 V                                                   |
| Energy efficiency class      | E                                                       |
| Energy consumption           | 13 kWh/1000h                                            |
| Frequency                    | 50HZ Hz                                                 |
| Power factor                 | 0.5                                                     |
| Useful luminous flux*        | 1500 lm (360°)                                          |
| Luminous flux**              | 1500 lm (360°)                                          |
| Lamp efficacy                | 115 lm/W                                                |
| Colour temperature           | 2700 / 3000 / 4000 / 5000 /<br>6500 K                   |
| Colour of light              | CCT                                                     |
| Beam angle                   | 270 °                                                   |
| RA                           | >80                                                     |
| Uniformity of color SDCM max | 5                                                       |
| Dimmable                     | No                                                      |
| Working temperature range    | -20 / +40 °                                             |
| Lifespan                     | 17000 h                                                 |
| Socket                       | E27                                                     |
| Dimension (AxBxC)            | 65x135 mm                                               |
| For use                      | Inside                                                  |
| Application                  | Inside                                                  |
| Made in                      | PRC                                                     |
| Other                        | Funkcja 5CCT 2700K / 3000K<br>/ 4000K / 5000K / 6500K , |

## Logistics data

|                       |           |
|-----------------------|-----------|
| Bulk packaging        | 100 pcs.  |
| Quantity per pallet   | 1600 pcs. |
| Gross weight (1 pcs.) | 0.075 kg  |

## Related documents



 Declaration of Conformity

