

NOCTIS MAX 2

SLI029079NW_PW

Floodlight NOCTIS MAX 2, with a power of 150 W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Narrow beam angle 85° gives directional light so that selected surfaces can be better exposed. Designed for surface mounting.



Power	150 W	Voltage	230 V
Luminous flux*	14250 lm (120°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	85 °
IK	08	Degree of protection (IP)	IP65

Technical data

Code	SLI029079NW_PW
Power	150 W
Nominal current	660 mA
Voltage	230 V
Energy consumption	150 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.99
Useful luminous flux*	14250 lm (120°)
Luminous flux**	14250 lm (360°)
Lamp efficacy	95 lm/W
Luminous intensity	8100 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	85 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	Aluminum+PC LENS
IK	08
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	304x269x38 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT

Logistics data

Bulk packaging	10 pcs.
Quantity per pallet	250 pcs.
Gross weight (1 pcs.)	1.32 kg

Related documents

 User manual Declaration of Conformity

