


|                        |                                                                                                                                                                                                                                                                                                    |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| article#               | <b>77723-4tt</b>                                                                                                                                                                                                                                                                                   |
| article description    | <b>CEE-flanged plug angled 32A 3p 4h IP44 TT</b>                                                                                                                                                                                                                                                   |
| description long       | CEE-flanged plug angled 32A 3p 4h IP44 TT<br>housing material: PC/ABS<br>rated current: 32A<br>number of poles: 3 (2P+PE)<br>clock-position: 4h<br>rated voltage/frequency: 100-130V~ / 50+60Hz<br>contacts: brass<br>connection technology: screwless terminals (TT)<br>IP protection class: IP44 |
| GTIN (EAN)             | 9003399347399                                                                                                                                                                                                                                                                                      |
| country of origin      | AT                                                                                                                                                                                                                                                                                                 |
| customs number         | 85366990                                                                                                                                                                                                                                                                                           |
| net weight             | 0.204 kg                                                                                                                                                                                                                                                                                           |
| packaging quantity     | 5                                                                                                                                                                                                                                                                                                  |
| minimum order quantity | 5                                                                                                                                                                                                                                                                                                  |

|                                 |                         |
|---------------------------------|-------------------------|
| ETIM 9.0                        | EC001319                |
| IEC-amperage                    | 32 A                    |
| Voltage according to EN 60309-2 | 110 V (50+60 Hz) yellow |
| Number of poles                 | 3                       |
| Clock hour position             | 4 h                     |
| Identification colour           | Yellow                  |
| Degree of protection (IP)       | IP44                    |
| Connection system               | Screw less terminal     |
| Construction type               | Built-up device plug    |
| Angle of plug                   | Angled                  |
| Material                        | Plastic                 |
| Contact material                | CuZn                    |
| Surface treatment contacts      | Untreated               |

|                        |                        |
|------------------------|------------------------|
| a                      | 90 mm                  |
| b                      | 100 mm                 |
| c                      | 77 mm                  |
| d                      | 85 mm                  |
| e                      | 163 mm                 |
| f                      | 100 mm                 |
| g                      | 5 mm                   |
| wire flexible          | 2,5-6 mm <sup>2</sup>  |
| wire solid             | 2,5-10 mm <sup>2</sup> |
| dismantling length     | 50 mm                  |
| stripping length       | 12-14 mm               |
| ambient temperature    | -25 – 40 °C            |
| temperature resistance | -25 – 80 °C            |



<https://www.pcelectric.at/shop/en/?func=detail&artnr=77723-4tt>