


|                        |                                                     |
|------------------------|-----------------------------------------------------|
| article#               | <b>80014-6</b>                                      |
| article description    | <b>Surface outlet 16A 4p 6h IP44</b>                |
| description long       | CEE-Aufputzdose 75x75 (blind) gerade 16A 4p 6h IP44 |
| GTIN (EAN)             | 9003399037436                                       |
| country of origin      | AT                                                  |
| customs number         | 85366990                                            |
| net weight             | 0.205 kg                                            |
| packaging quantity     | 10                                                  |
| minimum order quantity | 10                                                  |

|                                 |                      |
|---------------------------------|----------------------|
| ETIM 9.0                        | EC001321             |
| Model                           | Surface mounted      |
| IEC-amperage                    | 16 A                 |
| Number of poles                 | 4                    |
| Voltage according to EN 60309-2 | 400 V (50+60 Hz) red |
| Clock hour position             | 6 h                  |
| Identification colour           | Red                  |
| Degree of protection (IP)       | IP44                 |
| Connection system               | Screwed terminal     |
| Cable entry                     | None                 |
| Material                        | Plastic              |
| Contact material                | CuZn                 |
| Surface treatment contacts      | Untreated            |
| Type of fastening               | Inner lying mounting |

|                        |                       |
|------------------------|-----------------------|
| a                      | 104 mm                |
| b                      | 151 mm                |
| wire flexible          | 1-2,5 mm <sup>2</sup> |
| wire solid             | 1-4 mm <sup>2</sup>   |
| contact screws         | 100 Ncm               |
| connecting screws      | 110 Ncm               |
| dismantling length     | 50 mm                 |
| stripping length       | 10-12 mm              |
| ambient temperature    | -25 – 40 °C           |
| temperature resistance | -25 – 80 °C           |



<https://www.pcelectric.at/shop/en/?func=detail&artnr=80014-6>

