


|                        |                                                                                                                                                                                                                                                                                                                                                            |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| article#               | <b>414-7</b>                                                                                                                                                                                                                                                                                                                                               |
| article description    | <b>CEE-flanged socket sloping (70x85mm) 16A 4p 7h IP44</b>                                                                                                                                                                                                                                                                                                 |
| description long       | CEE-flanged socket sloping (70x85mm) 16A 4p 7h IP44<br>housing material: PA6<br>rated current: 16A<br>number of poles: 4 (3P+PE)<br>clock-position: 7h<br>rated voltage/frequency: 480-500V~ / 50+60Hz<br>contacts: brass<br>connection technology: screw terminals<br>dimensions (flange/fixing center): 70x85 mm / 50x65 mm<br>IP protection class: IP44 |
| GTIN (EAN)             | 9003399051920                                                                                                                                                                                                                                                                                                                                              |
| country of origin      | AT                                                                                                                                                                                                                                                                                                                                                         |
| customs number         | 85366990                                                                                                                                                                                                                                                                                                                                                   |
| net weight             | 0.127 kg                                                                                                                                                                                                                                                                                                                                                   |
| packaging quantity     | 10                                                                                                                                                                                                                                                                                                                                                         |
| minimum order quantity | 10                                                                                                                                                                                                                                                                                                                                                         |

|                                 |                        |
|---------------------------------|------------------------|
| ETIM 9.0                        | EC001317               |
| IEC-ampereage                   | 16 A                   |
| Voltage according to EN 60309-2 | 500 V (50+60 Hz) black |
| Number of poles                 | 4                      |
| Clock hour position             | 7 h                    |
| Identification colour           | Black                  |
| Degree of protection (IP)       | IP44                   |
| Connection system               | Screwed terminal       |
| Angle of plug                   | Angled                 |
| Material                        | Plastic                |
| Contact material                | CuZn                   |
| Surface treatment contacts      | Untreated              |
| Flange size vertical            | 85 mm                  |
| Drill hole distance vertical    | 65 mm                  |
| Flange size horizontal          | 70 mm                  |
| Drill hole distance horizontal  | 50 mm                  |

|                        |                       |
|------------------------|-----------------------|
| a                      | 70 mm                 |
| b                      | 85 mm                 |
| c                      | 50 mm                 |
| d                      | 65 mm                 |
| e                      | 38 mm                 |
| f                      | 47 mm                 |
| g                      | 56 mm                 |
| h                      | 67 mm                 |
| i                      | 5,5 mm                |
| j                      | 96 mm                 |
| k                      | 104 mm                |
| wire flexible          | 1-2,5 mm <sup>2</sup> |
| wire solid             | 1-4 mm <sup>2</sup>   |
| contact screws         | 100 Ncm               |
| dismantling length     | 50 mm                 |
| stripping length       | 10-12 mm              |
| ambient temperature    | -25 – 40 °C           |
| temperature resistance | -25 – 80 °C           |



<https://www.pceelectric.at/shop/en/?func=detail&artnr=414-7>