


|                        |                                                                                                                                                                                                                                                                                                                                                                      |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| article#               | <b>413-10f87</b>                                                                                                                                                                                                                                                                                                                                                     |
| article description    | <b>CEE-flanged socket sloping (75x85mm) 16A 3p 10h IP44/IP54</b>                                                                                                                                                                                                                                                                                                     |
| description long       | CEE-flanged socket sloping (75x85mm) 16A 3p 10h IP44/IP54<br>housing material: PA6<br>rated current: 16A<br>number of poles: 3 (2P+PE)<br>clock-position: 10h<br>rated voltage/frequency: >50V~ / 100-300Hz<br>contacts: brass<br>connection technology: screw terminals<br>dimensions (flange/fixing center): 75x85 mm / 60x60 mm<br>IP protection class: IP44/IP54 |
| country of origin      | AT                                                                                                                                                                                                                                                                                                                                                                   |
| customs number         | 85366990                                                                                                                                                                                                                                                                                                                                                             |
| packaging quantity     | 10                                                                                                                                                                                                                                                                                                                                                                   |
| minimum order quantity | 10                                                                                                                                                                                                                                                                                                                                                                   |

|                                 |                             |
|---------------------------------|-----------------------------|
| ETIM 9.0                        | EC001317                    |
| IEC-amperage                    | 16 A                        |
| Voltage according to EN 60309-2 | 50-500 V (100-300 Hz) green |
| Number of poles                 | 3                           |
| Clock hour position             | 10 h                        |
| Identification colour           | Green                       |
| Degree of protection (IP)       | IP44                        |
| Connection system               | Screwed terminal            |
| Angle of plug                   | Angled                      |
| Material                        | Plastic                     |
| Contact material                | CuZn                        |
| Surface treatment contacts      | Untreated                   |
| Flange size vertical            | 85 mm                       |
| Drill hole distance vertical    | 60 mm                       |
| Flange size horizontal          | 75 mm                       |
| Drill hole distance horizontal  | 60 mm                       |

|                        |                       |
|------------------------|-----------------------|
| a                      | 75 mm                 |
| b                      | 85 mm                 |
| c                      | 60 mm                 |
| d                      | 60 mm                 |
| e                      | 38 mm                 |
| f                      | 47 mm                 |
| g                      | 51 mm                 |
| h                      | 61 mm                 |
| i                      | 5,5 mm                |
| j                      | 85 mm                 |
| k                      | 99 mm                 |
| wire flexible          | 1-2,5 mm <sup>2</sup> |
| wire solid             | 1-4 mm <sup>2</sup>   |
| contact screws         | 100 Ncm               |
| dismantling length     | 50 mm                 |
| stripping length       | 10-12 mm              |
| ambient temperature    | -25 – 40 °C           |
| temperature resistance | -25 – 80 °C           |



<https://www.pcelectric.at/shop/en/?func=detail&artnr=413-10f87>