

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| article#               | <b>6124-7</b>                                                                                                                                                                                                                                                                                                                                                                                                                      |
| article description    | <b>CEE-switched interlocked socket compact 32A 4p 7h IP44/IP54</b>                                                                                                                                                                                                                                                                                                                                                                 |
| description long       | CEE-switched interlocked socket compact 32A4p 7h IP44/IP54<br>housing material: PA6 + PC/ABS<br>rated current: 32A<br>number of poles: 4 (3P+PE)<br>clock-position: 7h<br>rated voltage/frequency: 480-500V~ / 50+60Hz<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>wall mounting, mechanical interlock<br>switch: ON/OFF PCE-Merz ML0; EN 60947-3; AC22A, 10kA<br>IP protection class: IP44/IP54 |
| GTIN (EAN)             | 9003399175114                                                                                                                                                                                                                                                                                                                                                                                                                      |
| country of origin      | AT                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| customs number         | 85366990                                                                                                                                                                                                                                                                                                                                                                                                                           |
| net weight             | 0.695 kg                                                                                                                                                                                                                                                                                                                                                                                                                           |
| packaging quantity     | 1                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| minimum order quantity | 1                                                                                                                                                                                                                                                                                                                                                                                                                                  |

|                                 |                        |
|---------------------------------|------------------------|
| ETIM 9.0                        | EC001324               |
| IEC-amperage                    | 32 A                   |
| Number of poles                 | 4                      |
| Voltage according to EN 60309-2 | 500 V (50+60 Hz) black |
| Clock hour position             | 7 h                    |
| Identification colour           | Black                  |
| Degree of protection (IP)       | IP54                   |
| Switch                          | Mechanical locking     |
| Material housing                | Plastic                |
| Model                           | Base unit and cover    |
| Contact material                | CuZn                   |
| Surface treatment contacts      | Nickel-plated          |

|                        |                        |
|------------------------|------------------------|
| a                      | 123 mm                 |
| wire flexible          | 2,5-6 mm <sup>2</sup>  |
| wire solid             | 2,5-10 mm <sup>2</sup> |
| contact screws         | 120 Ncm                |
| housing screws         | 110 Ncm                |
| ambient temperature    | -25 – 40 °C            |
| temperature resistance | -25 – 80 °C            |



<https://www.pcelectric.at/shop/en/?func=detail&artnr=6124-7>

