


article#	75342-7
article description	CEE-switched interlocked socket 63A 4p 7h IP66/IP67
description long	CEE-switched interlocked socket 63A 4p 7h IP66/IP67 housing material: PC/ABS rated current: 63A number of poles: 4 (3P+PE) clock-position: 7h rated voltage/frequency: 480-500V~ / 50+60Hz contacts: brass, with lamellar spring (CuBe) connection technology: screw terminals wall mounting, mechanical interlock switch: ON/OFF PCE-Merz ML2-063; EN 60947-3; AC22A, 10kA cable entry: top, bottom or rear (incl. threaded blind cap) IP protection class: IP66/IP67
GTIN (EAN)	9003399077890
country of origin	AT
customs number	85366990
net weight	2.032 kg
packaging quantity	1
minimum order quantity	1

ETIM 9.0	EC001324
IEC-amperage	63 A
Number of poles	4
Voltage according to EN 60309-2	500 V (50+60 Hz) black
Clock hour position	7 h
Identification colour	Black
Degree of protection (IP)	IP67
Switch	Mechanical locking
Material housing	Plastic
Model	Base unit and cover
Contact material	CuZn
Surface treatment contacts	Nickel-plated

a	162 mm
b	310 mm
c	140 mm
d	240 mm
e	11 mm
f	184 mm
g	9 mm
wire flexible	6-25 mm ²
wire solid	6-35 mm ²
contact screws	250 Ncm
housing screws	200 Ncm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C



<https://www.pcelectric.at/shop/en/?func=detail&artnr=75342-7>