


|                        |                                                                                                                                                                                                                                                                                                                                                                                   |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| article#               | <b>382-10f5v</b>                                                                                                                                                                                                                                                                                                                                                                  |
| article description    | <b>CEE-flanged socket straight 55x55mm 16A 2p 24/42VDC IP44/IP54 TWIST</b>                                                                                                                                                                                                                                                                                                        |
| description long       | CEE-flanged socket straight 55x55mm 16A 2p 24/42VDC IP44/IP54 TWIST<br>housing material: PA6<br>rated current: 16A<br>number of poles: 2 (2P)<br>clock-position: 10h<br>rated voltage/frequency: 24/42V DC<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>dimensions (flange/fixing center): 55x55 mm / 45x45 mm<br>IP protection class: IP44/IP54 |
| GTIN (EAN)             | 9003399137709                                                                                                                                                                                                                                                                                                                                                                     |
| country of origin      | AT                                                                                                                                                                                                                                                                                                                                                                                |
| customs number         | 85366990                                                                                                                                                                                                                                                                                                                                                                          |
| net weight             | 0.112 kg                                                                                                                                                                                                                                                                                                                                                                          |
| packaging quantity     | 10                                                                                                                                                                                                                                                                                                                                                                                |
| minimum order quantity | 10                                                                                                                                                                                                                                                                                                                                                                                |

|                                 |                  |
|---------------------------------|------------------|
| ETIM 9.0                        | EC001317         |
| IEC-ampereage                   | 16 A             |
| Voltage according to EN 60309-2 | <50 V DC grey    |
| Number of poles                 | 2                |
| Clock hour position             | 10 h             |
| Identification colour           | White            |
| Degree of protection (IP)       | IP54             |
| Connection system               | Screwed terminal |
| Angle of plug                   | Straight         |
| Material                        | Plastic          |
| Contact material                | CuZn             |
| Surface treatment contacts      | Nickel-plated    |
| Flange size vertical            | 55 mm            |
| Drill hole distance vertical    | 45 mm            |
| Flange size horizontal          | 55 mm            |
| Drill hole distance horizontal  | 45 mm            |

|                        |                        |
|------------------------|------------------------|
| a                      | 55 mm                  |
| b                      | 55 mm                  |
| c                      | 45 mm                  |
| d                      | 45 mm                  |
| e                      | 19 mm                  |
| f                      | 47 mm                  |
| g                      | 4,5 mm                 |
| h                      | 43 mm                  |
| i                      | 79 mm                  |
| j                      | 93 mm                  |
| wire flexible          | 1-10 mm <sup>2</sup>   |
| wire solid             | 1,5-10 mm <sup>2</sup> |
| contact screws         | 160 Ncm                |
| dismantling length     | 70 mm                  |
| stripping length       | 14-16 mm               |
| ambient temperature    | -25 – 40 °C            |
| temperature resistance | -25 – 80 °C            |



<https://www.pceelectric.at/shop/en/?func=detail&artnr=382-10f5v>