


article#	382-12f8v
article description	CEE-flanged socket straight 60x70mm 16A 2p 42VAC 50/60Hz IP44/IP54 TWIST
description long	CEE-flanged socket straight 60x70mm 16A 2p 42VAC 50/60Hz IP44/IP54 TWIST housing material: PA6 rated current: 16A number of poles: 2 (2P) clock-position: 12h rated voltage/frequency: 42V~ / 50+60Hz contacts: brass nickel plated connection technology: screw terminals dimensions (flange/fixing center): 60x70 mm / 47x53 mm IP protection class: IP44/IP54
GTIN (EAN)	9003399001598
country of origin	AT
customs number	85366990
net weight	0.112 kg
packaging quantity	10
minimum order quantity	10

ETIM 9.0	EC001317
IEC-ampereage	16 A
Voltage according to EN 60309-2	40-50 V (50+60 Hz) white
Number of poles	2
Clock hour position	12 h
Identification colour	White
Degree of protection (IP)	IP54
Connection system	Screwed terminal
Angle of plug	Straight
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated
Flange size vertical	70 mm
Drill hole distance vertical	53 mm
Flange size horizontal	60 mm
Drill hole distance horizontal	47 mm

a	60 mm
b	70 mm
c	47 mm
d	53 mm
e	19 mm
f	47 mm
g	5,5 mm
h	43 mm
i	86 mm
j	93 mm
wire flexible	1-10 mm ²
wire solid	1,5-10 mm ²
contact screws	160 Ncm
dismantling length	70 mm
stripping length	14-16 mm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C



<https://www.pceelectric.at/shop/en/?func=detail&artnr=382-12f8v>