

# SHIFT NANO STRIPE M

WLD+80009

SYSTEM SHIFT NANO - STRIPE M TO TRACK 547X6X10MM 6W WHITE 5Y WARRANTY



|                    |               |
|--------------------|---------------|
| Power              | <b>6 W</b>    |
| Colour temperature | <b>3000 K</b> |
| Beam angle         | <b>120 °</b>  |

|                           |             |
|---------------------------|-------------|
| Voltage                   | <b>48 V</b> |
| Colour of light           | <b>WW</b>   |
| Degree of protection (IP) | <b>IP20</b> |

## Technical data

|                              |               |
|------------------------------|---------------|
| Code                         | WLD+80009     |
| Power                        | 6 W           |
| Nominal current              | 100 mA        |
| Voltage                      | 48 V          |
| Energy consumption           | 6 kWh/1000h   |
| Frequency                    | DC Hz         |
| Protection class             | III           |
| Power factor                 | 1             |
| Useful luminous flux*        | 500 lm (360°) |
| Luminous flux**              | 150 lm (360°) |
| Lamp efficacy                | 83 lm/W       |
| Colour temperature           | 3000 K        |
| Colour of light              | WW            |
| Beam angle                   | 120 °         |
| RA                           | >90           |
| Light source included        | Yes           |
| Uniformity of color SDCM max | 5             |
| Dimmable                     | No            |
| Working temperature range    | -20 to +40 °  |
| Lifespan                     | 50000 h       |
| Housing material             | SILIKON       |
| Degree of protection (IP)    | IP20          |
| Colour                       | White         |
| Dimension (AxBxC)            | 547x6x10 mm   |
| For use                      | Inside        |
| Assembly method              | on track 48V  |
| Application                  | Inside        |
| Made in                      | PRC           |

## Logistics data

|                       |           |
|-----------------------|-----------|
| Bulk packaging        | 100 pcs.  |
| Gross weight (1 pcs.) | 0.0517 kg |

## Related documents

 User manual Declaration of Conformity

