

# SHIFT NANO GRID S

WLD+80014

SYSTEM SHIFT NANO - GRID S LINEAR TRACKLIGHT 196X12X30MM 10W 24DEG BLACK 5Y WARRANTY



|                           |               |
|---------------------------|---------------|
| Power                     | <b>12 W</b>   |
| Colour temperature        | <b>3000 K</b> |
| Beam angle                | <b>24 °</b>   |
| Degree of protection (IP) | <b>IP20</b>   |

|                 |               |
|-----------------|---------------|
| Voltage         | <b>48 V</b>   |
| Colour of light | <b>WW</b>     |
| UGR             | <b>&lt;19</b> |

## Technical data

|                              |                |
|------------------------------|----------------|
| Code                         | WLD+80014      |
| Power                        | 12 W           |
| Nominal current              | 220 mA         |
| Voltage                      | 48 V           |
| Energy consumption           | 12 kWh/1000h   |
| Frequency                    | DC Hz          |
| Protection class             | III            |
| Power factor                 | 1              |
| Useful luminous flux*        | 1180 lm (360°) |
| Luminous flux**              | 500 lm (360°)  |
| Lamp efficacy                | 98 lm/W        |
| Luminous intensity           | 1600 cd        |
| Colour temperature           | 3000 K         |
| Colour of light              | WW             |
| Beam angle                   | 24 °           |
| UGR                          | <19            |
| RA                           | >90            |
| Light source included        | Yes            |
| Uniformity of color SDCM max | 5              |
| Dimmable                     | No             |
| Working temperature range    | -20 to +40 °   |
| Lifespan                     | 50000 h        |
| Housing material             | Aluminum       |
| Degree of protection (IP)    | IP20           |
| Colour                       | Black          |
| Dimension (AxBxC)            | 196x12x30 mm   |
| For use                      | Inside         |
| Assembly method              | on track 48V   |
| Application                  | Inside         |
| Made in                      | PRC            |

## Logistics data

|                       |           |
|-----------------------|-----------|
| Bulk packaging        | 50 pcs.   |
| Gross weight (1 pcs.) | 0.1075 kg |

## Related documents

 User manual Declaration of Conformity

