









- Universal: Supports ATX, ITX, Micro-ATX, and SSI CEB boards.
- Cooling: 3 x 80 mm PWM fans (900-2600 RPM, 26.1 dB, 50,000 h).
- Drive bays: 4x 2.5" and 6x 3.5".
- Durable: Galvanized steel 1.2 mm.
- I/O panel: 2x USB 3.0, Power, and Reset.
- Accessories: PSU adapters (ATX, SFX, Flex ATX), PWM splitter, dust filter.







ICT height	2 U
Size	19",
Motherboard form factor	ATX, ITX, Micro-ATX, SSI CEB
Number of installed fans	3
Installed fans	3x 80 mm PWM
Rotational speed	from 900 up to 2 600 RPM
Fan lifetime	50 000 h
Maximum CPU cooling height	72 mm
Fan noise level	26.10 dB
Number of 2.5" drive bays (SSD/HDD)	4
Number of 3.5" drive bays (SSD/HDD)	6
Number of expansion slots	7
Compatible power supply standard	ATX, FLEX, SFX
Connectors	USB 3.0 Type-A
Material	Steel, Galvanized steel
Working depth	520 mm
Upper & lower panel thickness	1,2 mm
Side panel thickness	1,2 mm
Other elements sheet thickness	1,2 mm
Dimensions	520 x 430 x 89 mm
Weight	7,5 kg
Included Accessories	Flex ATX power supply mounting adapter, 1U custom power supply mounting adapter (100mm wide), ATX, SFX power supply mounting adapter, Flex ATX power supply rear mounting bracket, PWM 4-PIN fan splitter,

Replaceable front dust filter