

PowerWalker VI 1200 LCD/FR

Line-Interactive UPS System

1200VA Line-Interactive UPS

1200VA Line-Interactive UPS

2x French + 2x IEC outlets, RJ11/RJ45 Surge Protection


USB Connection for monitoring

Cold start, built-in boost and buck AVR function

LCD display for status view



Item-No. 10121002



Product Features

PowerWalker VI 1200 LCD/FR is a Line- Interactive UPS which provides high performance and reliable and cost-effective backup power protection. The UPS can be automatically started up without AC power supplied. In addition, this UPS provides RJ11/RJ45 surge protection. Equipped with a voltage stabilizer, this UPS will continue providing clean and stable power to connected equipment and is perfect for any home or SMB (small medium business) application.

- Super smart charger to shorten charging time
- Built-in boost and buck AVR
- Simulated sine wave
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function
- USB communication port
- RJ11/RJ45 surge protection
- Monitoring software included
- LCD Display show UPS status



Backside view



LCD status view



USB port,
RJ11/45 surge protection

Technical Details

Product Features

Capacity	1200VA/600W
Input Voltage	230 VAC
Input Voltage Range	170-280VAC $\pm 7\%$
Output Voltage	230 VAC
Voltage Regulation (Battery Mode)	$\pm 10\%$
Output Frequency	50Hz or 60Hz
Frequency Regulation (Battery Mode)	$\pm 1\text{Hz}$
Output Waveform	Simulated Sine Wave

Battery

Type	12V / 7Ah
Quantity	2x
Recharge Time	6h for 90% after complete discharge

Transfer Time

Typical	4-8 ms
---------	--------

LCD Indicators

Indicators	AVR mode, Battery mode, Load level, Battery capacity, Input voltage, Output voltage, Overload alarm, Fault alarm, and Low battery alarm
------------	---

Audio Indicators

Battery Mode	Beep every 10 sec
Low Battery	Beep every second
Fault	Continuous Beep
Overload	Beep every 0.5 sec

Full Protection

Discharge prevention	Yes
Deep discharger	Yes
Overcharge	Yes
Overload	Yes

Connections

Interface	USB
Outlets	2x French, 2x IEC
Surge Protection	RJ11/RJ45 (in/out)

Software & System Requirements

Software	WinPower
Operating System	For details visit: www.powerwalker.com/winpower.html
Other	1x USB port

Product Details

Dimensions	365 x 139 x 195 mm
Colour	Black
Weight	8.9 kg
Model Code	VI 1200 LCD/FR

Environment

Temperature	0°C – 40°C
Humidity	0% - 90% RH (non-condensing)

Package Content

Package Content	PowerWalker VI 1200 LCD/FR, Input Power Cable, USB cable, Software CD, Manual
-----------------	---

Logistic Data

Giftbox Language	EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KZ/RS
Manual Language	EN/DE/FR/PL
Dimension/Giftbox	452 x 230 x 292 mm
Weight/Giftbox	9.4 kg
Pieces/Carton	1 pcs
Pieces/Palette	42 pcs
Item Number	10121002
EAN	4260074976533
Warranty	24 Month (except battery)



Optional Accessory:
2x Yuasa 12V/7Ah battery
Datasheet: [Link](#)
CSB or Panasonic brand can also be used

Use UPS configurator on www.powerwalker.com for detailed backup time information.

Version: EN 18/07/2014
We reserve the right for technical changes and mistakes

PowerWalker is a brand of:
BlueWalker GmbH
Martin-Buber-Strasse 12 • D-41470 Neuss • Germany

Phone: +49 (0) 2137 / 92 98 73 • Fax: +49 (0) 2137 / 78 73 925
info@bluewalker.eu • www.bluewalker.eu • www.powerwalker.com