

# armac-

## UPS ARMAC

OFFICE ON-LINE PF1 1000VA  
DUST FREE



### PRODUCT SPECIFICATION:

|                                    |                                                                                      |
|------------------------------------|--------------------------------------------------------------------------------------|
| UPS topology                       | On-line (VFI)                                                                        |
| Power                              | 1 000 W                                                                              |
| PowerFactor                        | 1                                                                                    |
| Device efficiency                  | 94,5 %                                                                               |
| Type of casing                     | Rack                                                                                 |
| Number of outlets                  | 8                                                                                    |
| Outlet type                        | IEC C13                                                                              |
| Battery quantity                   | 3                                                                                    |
| Connectors                         | RS-232, USB Type-B                                                                   |
| Battery pack connector             | Yes                                                                                  |
| Battery capacity                   | 9 Ah                                                                                 |
| Battery type                       | Lead acid VRLA AGM                                                                   |
| Battery voltage                    | 12 V                                                                                 |
| Recharge time                      | 6 h                                                                                  |
| Input voltage                      | 230 V                                                                                |
| Input voltage range                | from 110 up to 300 V                                                                 |
| Input frequency range              | from 40 up to 70 Hz                                                                  |
| Output voltage                     | 230 V                                                                                |
| Output acceptable voltage range    | from 208 up to 240 V                                                                 |
| Output frequency                   | 60 Hz                                                                                |
| Automatic Voltage Regulation (AVR) | Yes                                                                                  |
| Waveform type                      | Full sine wave                                                                       |
| AC/DC Transfer time                | from 0 up to 0 ms                                                                    |
| Cold start                         | Yes                                                                                  |
| Protections                        | Interference filter, Overload protection, Short circuit protection, Surge protection |
| Noise level                        | 50 dB                                                                                |
| Colour                             | Black                                                                                |
| Software                           | PowerManager II                                                                      |
| Supported Operating Systems        | Linux, Unix, Windows 7, Windows 7 64bit, Windows 10, Windows 10 64bit, Windows 11    |
| Weatherproof rating                | IP20                                                                                 |
| ICT height                         | 2 U                                                                                  |
| Dimensions                         | 385 x 438 x 88 mm                                                                    |
| Weight                             | 13,5 kg                                                                              |

EAN-13: 5901969446999  
CAT. NO: R/1000I/PF1/DF

Despite all efforts, the manufacturer / distributor / seller does not guarantee that the published technical data, photos and descriptions do not contain any deficiencies or mistakes. The above catalogue is for information purposes and does not constitute an offer within the meaning of the Civil Code.