

NOCTIS LUX 4

SLI029074WW_PW

Floodlight NOCTIS LUX 4, with a power of 10 W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK07 class provides impact resistance. It shines with a warm light (3000K). Designed for surface mounting.

IP65

IK07



Power	10 W
Luminous flux*	750 lm (120°)
Colour of light	WW
IK	07

Voltage	230 V
Colour temperature	3000 K
Beam angle	100 °
Degree of protection (IP)	IP65

Technical data

Code	SLI029074WW_PW
Power	10 W
Nominal current	50 mA
Voltage	230 V
Energy consumption	10 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	750 lm (120°)
Luminous flux**	750 lm (360°)
Lamp efficacy	75 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	94x78x24 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC

Logistics data

Bulk packaging	40 pcs.
Quantity per pallet	800 pcs.
Gross weight (1 pcs.)	0.171 kg

Related documents

 User manual Declaration of Conformity

