

VERSA CCT

SLI003050CCT_PW

Façade luminaire VERSA CCT with the possibility of changing the light color (CCT), with a power of 15 W, high light efficacy 140 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 2700/4000/6000K, we can adjust the light color depending on our needs and preferences. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. Designed for surface mounting.

CCT

IP65



Power	15 W	Voltage	230 V
Luminous flux*	2100 lm (360°)	Colour temperature	2700 / 4000 / 6000 K
Colour of light	CCT	Beam angle	100 °
Degree of protection (IP)	IP65		

Technical data

Code	SLI003050CCT_PW
Power	15 W
Nominal current	112 mA
Voltage	230 V
Energy consumption	15 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.5
Useful luminous flux*	2100 lm (360°)
Luminous flux**	1500 lm (360°)
Lamp efficacy	140 lm/W
Colour temperature	2700 / 4000 / 6000 K
Colour of light	CCT
Beam angle	100 °
RA	80
Light source included	+
Dimmable	No
Working temperature range	-20 / +40 °
Lifespan	17000 h
Housing material	Plastic
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	196x180x70 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT / EXT
Made in	PRC
Other	Light color change function 2700K / 4000K / 6000K ,

Logistics data

Bulk packaging	20 pcs.
Quantity per pallet	240 pcs.
Gross weight (1 pcs.)	0.65 kg

Related documents

 User manual Declaration of Conformity

