

# ALGINE DOPPIO

SLI035092NW\_PW

LED panel ALGINE DOPPIO, with a power of 40 W, high light efficacy 150 lm/W. It is made of high-quality components, supported by a 5-year warranty. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Narrow beam angle 80° gives directional light so that selected objects or surfaces can be better exposed. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	<b>40 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>6000 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>80 °</b>
Degree of protection (IP)	<b>IP20</b>		



## Technical data

## Logistics data

Code	SLI035092NW_PW
Power	40 W
Nominal current	175 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	SPECTRUM
Power factor	0.97
Useful luminous flux*	6000 lm (360°)
Luminous flux**	5200 lm (360°)
Lamp efficacy	150 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	80 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Lifespan	50000 h
Housing material	Aluminum / Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x35 mm
Mounting hole	575x575mm mm
For use	Inside
Application	INT
Made in	PL
Other	zawiera 2 źródła św. fi use=3000 20W NW ,

Bulk packaging 5 pcs.

## Related documents

 User manual Declaration of Conformity

