

Technical drawings of the SW19 pump assembly, showing dimensions in millimeters (mm):

- Top View:** Overall width 100 mm, height 42 mm. Mounting holes are spaced 33.5x6.0 mm. A central hole has a diameter of 9 mm. The distance from the center to the mounting holes is 17.5 mm.
- Front View (Left):** Overall height 30 mm. The main body has a diameter of 23 mm. The mounting flange has a diameter of 9 mm. The distance from the center to the mounting holes is 8.5 mm. The overall length is 103.5 mm.
- Front View (Right):** Overall height 30 mm. The main body has a diameter of 16 mm. The mounting flange has a diameter of 9 mm. The distance from the center to the mounting holes is 39 mm.
- Bottom View:** Overall width 113x18 mm. The mounting flange has a diameter of 17 mm. The distance from the center to the mounting holes is 50 mm.
- Mounting Holes:** The mounting holes are spaced 33.5x6.0 mm. The distance from the center to the mounting holes is 17.5 mm.
- Mounting Holes:** The mounting holes are spaced 33.5x6.0 mm. The distance from the center to the mounting holes is 17.5 mm.

Typ Nr kat.	HVI P LO ASS RAV KF 27 V2A 819 149
Materiał	stal nierdzewna
Przylączenie	Sworzeń Ø10 mm, dł. 50 mm
Średnica zewnętrzna Ø	30 mm
Śruba	Sworzeń gwintowany M8 x 10 mm
Odniesienie do norm	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Waga	757 g
Numer taryfy celnej (Nomenklatura scalona EU)	85359000
GTIN (EAN)	4013364272057
Jed. Op.	1 szt.

Strona 1 / 1