


NOCTIS LUX 4

SLI029069NW_PW

Floodlight NOCTIS LUX 4, with a power of 100 W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK07 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Designed for surface mounting.

IP65

IK07



Power	100 W	Voltage	230 V
Luminous flux*	8700 lm (120°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	100 °
IK	07	Degree of protection (IP)	IP65

Technical data

Code	SLI029069NW_PW
Power	100 W
Nominal current	425 mA
Voltage	230 V
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	8700 lm (120°)
Luminous flux**	8700 lm (360°)
Lamp efficacy	87 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	251x207x26 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC

Logistics data

Bulk packaging	10 pcs.
Quantity per pallet	240 pcs.
Gross weight (1 pcs.)	0.947 kg

Related documents



 Declaration of Conformity

