


Niloé™

IP 44 Socket outlets

Cat. Nos: NP3108BK/MG/WH, NP3128BK/MG/WH






1. USE

2 P+E sealed socket outlets with shutters. Supplied with cover plates and support frames. To be fitted with single module or multi-module plates. Screws fixing.

2. RANGE

Designation	White	Medium Grey	Black
IP44 2P+E SOCKET FRENCH STANDARD AUTO TERMI- NALS SHUTTERED	NP3108WH	NP3108MG	NP3108BK
IP44 2P+E SOCKET GERMAN STANDARD AUTO TERMI- NALS SHUTTERED	NP3128WH	NP3128MG	NP3128BK

3. DIMENSIONS (mm)



References	Α	В	С	D
NP3108	91.9	86	29.4	15.7
NP3128	91.9	86	29.4	18.7

4. CONNECTION

Type of terminals: automatics Terminals capacity: 2 x 2.5 mm² Compatible flexible or rigid cables. Stripping length: 12 mm

5. TECHNICAL CHARACTERISTICS

■ 5.1 Mecanical characteristics

Protection against solid bodies and liquids: IP 44 Protection against impacts: IK 04

■ 5.2 Material characteristics

Polyglass appearance

Material: - Cover plates: PC

- UV resistant

Material of the support: - PC grey RAL 7016 + 10 % glass fiber

- Halogen free

Self-extinguishing:

- + 850° C / 30 s for insulating parts holding live parts in place
- $+650^{\circ}$ C / 30 s for other parts made of insulating materials

■ 5.3 Electrical characteristics

Voltage: 250 V~ Current: 16 A Frequency: 50/60 Hz

■ 5.4 Climatic characteristics

Storage temperature: -10°C to +70°C Usage temperature: -5°C to +40°C

6. CLEANING

Surface cleaning with a cloth.

Do not use: acetone, tar remover, trichloroethylene.

Resistance to the cleaning agents: Hexane, Methylated spirit, Soapy water, Diluted ammonia, Diluted pure bleach 10%, Glass cleaning substances, Pre-impregnated wipes.

Caution: A preliminary test should be carried out if other specific cleaning products are to be used.

7. STANDARDS AND APPROVALS

The undersigned, LEGRAND, declares that the radio-electric equipment type (Cat. Nos: NP3108BK/MG/WH - NP3128BK/MG/WH) complies with directive 2014/53/EU.

The full text of the EU declaration of conformity is available on the following website: www.legrand.com/ecatalogue