



Niloé™

Socket outlets - French Standard

Cat. No(s): NP3111BK/MG/WH/ NP3112BK/MG/WH





1. USE

Socket outlets with or without shutters.

Mechanisms supplied with protection cover.

To be equipped with plates one or several gangs.


Flush-mounting or surface-mounting.

Screw or claw fixing.

2. RANGE

Description	White	Medium Grey	Black
2X 2 P+E socket screw terminal	NP3111WH	NP3111MG	NP3111BK
2X 2 P+E socket shutters screw terminal	NP3112WH	NP3112MG	NP3112BK

3. DIMENSIONS (mm)



4. CONNECTION

Capacity: 2 x 2.5 mm² Flexible or rigid cables compatible Type of terminals: automatic Stripping length: 10 mm

5. TECHNICAL CHARACTERISTICS

■5.1 Mechanical characteristics

Protection against solid bodies and liquids: IP 20 Protection against impact: IK 04

■5.2 Material characteristics

Polygloss appearance

Material: - Mechanism housing + Support: PC+SUP

- Claws: steel

Self-extinguishing:

- $+\,850^{\circ}\,\text{C}\,/\,30\,\text{s}$ for insulating parts holding live parts in place
- $+650^{\circ}$ C / 30 s for other parts made of insulating materials

■5.3 Electrical characteristics

Voltage: 250 V~ Current: 16 A Frequency: 50/60 Hz

■5.4 Climatic characteristics

Storage temperature: - 10° C to $+70^{\circ}$ C Usage temperature: - 5° C to $+40^{\circ}$ C

6. MAINTENANCE

Surface cleaning with a cloth.

Do not use: acetone, tar remover, trichloroethylene.

Maintenance with the following products: Hexane, Methylated spirit, Soapy water, Diluted ammonia, Bleach diluted to 10%, Window-cleaning products.

Caution: A preliminary test should be carried out if other specific cleaning products are to be used.

7. STANDARDS AND APPROVALS

The undersigned, LEGRAND, declares that the radio-electric equipment type (Cat. Nos NP3111BK/MG/WH - NP3112BK/MG/WH) complies with directive 2014/53/EU.

The full text of the EU declaration of conformity is available on the following website: www.legrand.com/ecatalogue