

AGRO synthetic cable glands Progress® GFK increased safety Ex e II and intri



Entry thread metric

Type approval: Progress GFK EX

- Black / light blue RAL 5012_x000D_
- One-piece sealing insert

Order number:	EX1530.25.190
E-No:	121765628
EAN:	7611614176741
Material	Polyamide glass fiber reinforced
Properties	halogen-free
Seal	TPE / NBR
Operation temperature	-20°C / +85°C
Protection class	IP 66 / IP 68
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Gas	II 2G Ex eb IIC Gb
Dust	II 2D Ex tb IIIC Db
Intrinsic safety gas	II 2G Ex ia IIC Ga
Intrinsic safety dust	II 2D Ex ia IIIC Da
Zone	Gas 0, 1 and 2 / dust 20, 21 and 22
Certificate	SEV 15 ATEX 0152X
IECEx Certificate	IECEx SEV 15.0019X
Entry thread	M25x1.5
Clamping range without insert min.	16.0 mm
Clamping range without insert max.	19.0 mm
Wrench size	34 mm
Dimension H	33 mm
Thread length L	13 mm
Dispatch	25

3 = Material sealing insert NBR

Available on request:

- For installation of multiple cables