

## AGRO synthetic cable glands Progress® GFK increased safety Ex e II



### Entry thread metric

#### Type approval: Progress GFK EX

- Black RAL 9005
- One-piece sealing insert

|                                    |                                                   |
|------------------------------------|---------------------------------------------------|
| <b>Order number:</b>               | <b>EX1540.40.330</b>                              |
| E-No:                              | 121761838                                         |
| EAN:                               | 7611614176420                                     |
| Material                           | Polyamide glass fiber reinforced                  |
| Properties                         | halogen-free                                      |
| Seal                               | TPE / NBR                                         |
| Operation temperature              | -20°C / +85°C                                     |
| Protection class                   | IP 66 / IP 68                                     |
| Test standard                      | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                                | II 2G Ex eb IIC Gb                                |
| Dust                               | II 2D Ex tb IIIC Db                               |
| Zone                               | Gas 1 and 2 / dust 21 and 22                      |
| Certificate                        | SEV 15 ATEX 0152X                                 |
| IECEx Certificate                  | IECEx SEV 15.0019X                                |
| Entry thread                       | M40x1.5                                           |
| Clamping range without insert min. | 30.0 mm                                           |
| Clamping range without insert max. | 33.0 mm                                           |
| Wrench size                        | 50 mm                                             |
| Dimension H                        | 40 mm                                             |
| Thread length L                    | 15 mm                                             |
| Dispatch                           | 10                                                |

3 = Material sealing insert NBR