

## AGRO cable glands Progress® nickel-plated brass increased safety Ex e II



### Long entry thread Pg

#### Type approval: Progress MS EX

- One-piece sealing insert
- not overall length insulated

|                                    |                                                   |
|------------------------------------|---------------------------------------------------|
| <b>Order number:</b>               | <b>EX1100.36.305</b>                              |
| EAN:                               | 7611614178479                                     |
| Material                           | Nickel-plated brass                               |
| Seal                               | TPE                                               |
| O-ring                             | FPM                                               |
| Operation temperature              | -60°C / +100°C                                    |
| Protection class                   | IP 66 / IP 68 (up to 10 bar)                      |
| Test standard                      | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                                | II 2G Ex eb IIC Gb                                |
| Dust                               | II 2D Ex tb IIIC Db                               |
| Zone                               | Gas 1 and 2 / dust 21 and 22                      |
| Certificate                        | SEV 15 ATEX 0152X                                 |
| IECEx Certificate                  | IECEx SEV 15.0019X                                |
| Entry thread                       | Pg 36                                             |
| Clamping range without insert min. | 26.0 mm                                           |
| Clamping range without insert max. | 30.5 mm                                           |
| Wrench size                        | 50 mm                                             |
| Dimension H                        | 32 mm                                             |
| Thread length L                    | 15 mm                                             |
| Dispatch                           | 10                                                |

#### Available on request:

- Executions in steel A2 and A4, entry thread NPT