AGRO cable glands Progress® nickel-plated brass increased safety Ex e II for



Short entry thread metric

Type approval: Progress MS Multi EX

- One-piece sealing insert
- not overall length insulated

Order number:	**EX1310.63.3.180**
EAN:	7611614240763
Material	Nickel-plated brass
Seal	TPE / NBR
O-ring	FPM
Operation temperature	-60°C / +100°C
Protection class	IP 66 / IP 68
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Gas	II 2G Ex eb IIC Gb
Dust	II 2D Ex tb IIIC Db
Zone	Gas 1 and 2 / dust 21 and 22
Certificate	SEV 15 ATEX 0152X
IECEx Certificate	IECEx SEV 15.0019X
Entry thread	M63x1.5
Clamping range without insert min.	17.0 mm
Clamping range without insert max.	18.0 mm
Number of cables	3
Wrench size	70 mm
Dimension H	37 mm
Dimension L	10 mm
Note	3
Dispatch	5

3 = Material sealing insert NBR
Suitable locking pins see accessories

Available on request:
- Executions in steel A2 and A4, entry thread NPT

Data weryfikacji 07.10.2025 | Dystrybucja ASTAT