# AGRO cable glands Progress® nickel-plated brass increased safety Ex e II for




## Short entry thread metric

**Type approval: Progress MS Multi EX**

- One-piece sealing insert
- not overall length insulated

| **Order number:** | **EX1310.63.6.120** |
|---|---|
| EAN: | 7611614239378 |
| Material | Nickel-plated brass |
| Seal | TPE / NBR |
| O-ring | FPM |
| Operation temperature | -60°C / +100°C |
| Protection class | IP 66 / IP 68 |
| Test standard | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas | II 2G Ex eb IIC Gb |
| Dust | II 2D Ex tb IIIC Db |
| Zone | Gas 1 and 2 / dust 21 and 22 |
| Certificate | SEV 15 ATEX 0152X |
| IECEx Certificate | IECEx SEV 15.0019X |
| Entry thread | M63x1.5 |
| Clamping range without insert min. | 11.0 mm |
| Clamping range without insert max. | 12.0 mm |
| Number of cables | 6 |
| Wrench size | 70 mm |
| Dimension H | 37 mm |
| Dimension L | 10 mm |
| Note | 3 |
| Dispatch | 5 |

3 = Material sealing insert NBR
Suitable locking pins see accessories

**Available on request:**
- Executions in steel A2 and A4, entry thread NPT



Data weryfikacji 07.10.2025 | Dystrybucja ASTAT